



All Models    **A** 12"    **B** 47"    **C** 12"

### Key Features

- Ready for "Plug n Play" installation
- Adjustable fan speed control
- Flexible wall mount or ceiling joist mount
- May be ducted up to 8 feet from cellar
- Black exterior to hide unit behind a wood grill
- Extremely quiet in cellar operation
- 55 degree temperature differential

### Specifications

Model	HM2500-S	HM3500-S	HM5000-S	HM6500-S
Cellar Size (Cu. Ft.)	650	1000	1500	2000
BTUh @ 55°	3100	3500	≈4100	6500
CFM	214	252	456	456
Dimensions	47"W x 12"H x 12"D			
Refrigerant	R-134a	R-134a	R-134a	R-134a
HP	1/4	1/3	1/3++	1/2
Voltage Rating (20 amp dedicated circuit required)	110V or 220V	110V or 220V	110V or 220V	110V or 220V
Coil Weight (lbs)	60	60	65	65
AMPS (Starting/Running)	Evaporator: 1.4/1.04 Condenser: 28/5.4	Evaporator: 1.4/1.14 Condenser: 32.7/7.2	Evaporator: 2.5/2 Condenser: 40/8.2	Evaporator: 2.5/2.1 Condenser: 58.8/11.3
dBA (Evaporator)	48	56	56	59
Drainline	1/2" Condensate			
Installation	Evaporator coil installed in the cellar or up to 8 feet away. Condenser up to 100 line feet away.			
Thermostat	Advanced electronic control system remote			
Temp. Delta	55° F			
Warranty	2 year parts and labor			

### Optional Accessories

Duct kit, exterior condenser housing

