



	A	B	C
Ultimate 3300	15.75"	14.25"	26"
Ultimate 4400	15.75"	14.25"	26"
Ultimate 8800	22"	14.25"	27.5"

Key Features

- Variable speed fans
- Operates in extreme environments
- 55 degree temperature differential
- Flexible mounting bracket
- Control mounted on front of unit or remote
- Ductable exterior exhaust

Specifications

Model	Ultimate 3300	Ultimate 4400	Ultimate 8800
Cellar Size (Cu. Ft.)	800	1250	2000
BTUh @ 55°	2688	4200	5760
CFM	256	256	283
Dimensions	14.25"W x 15.75"H x 26"D		14.25"W x 22"H x 27.5"D
Refrigerant	R-134a	R-134a	R-134a
HP	1/4+	1/4+	3/4+
Voltage Rating (20 amp dedicated circuit required)	110V or 220V	110V or 220V	110V or 220V
Weight (lbs)	115	115	150
AMPS (Starting/Running)	32 / 9	32 / 9	36 / 17
dBA (Low/Medium/High)	51 / 58 / 66	51 / 58 / 66	57 / 59 / 61
Drainline	1/2" Condensate		
Installation	Through-the-Wall, partially ducted, fully ducted		
Thermostat	Advanced electronic control system		
Temp. Delta	55°F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 110°F)		
Outside Venting	Can be done if the outside temperature does not exceed 110°F, the external grille cover is highly recommended		
Ducting Options	Unit can be fully ducted		
Warranty	2 year parts and labor		

Optional Accessories

Advanced electronic control system remote, ducting plenum, exterior grille

