



	A	B	C
WM2500-C	10.5"	20"	11.25"
WM3500-C	15.5"	20.5"	14.5"
WM5000-C	15.5"	20.5"	14.5"

Key Features

- Ready for "plug n play" installation
- Adjustable fan speed control
- Flexible wall mounting coils
- Quiet & efficient in cellar operation
- 55 degree temperature differential
- Advanced electronic control system

Specifications

Model	WM2500-S	WM3500-S	WM5000-S
Cellar Size (Cu. Ft.)	500	1000	2000
BTUh @ 55°	1620	4715	6006
CFM	94	270	278
Dimensions	Evaporator: 20"W x 10.5"H x 11.25"D Condenser: 11.5"W x 10.5"H x 14"D	Evaporator: 20.56"W x 15.5"H x 14.5"D Condenser: 13.25"W x 14.75"H x 16"D	Evaporator: 20.56"W x 15.5"H x 14.5"D Condenser: 13.25"W x 14.75"H x 16"D
Refrigerant	R-134a	R-134a	R-134a
HP	1/5	1/2	1/2+
Voltage Rating (20 amp dedicated circuit required)	110V or 220V	110V or 220V	110V or 220V
Weight (lbs)	Evaporator: 25, Condenser: 36	Evaporator: 56, Condenser: 56	Evaporator: 56, Condenser: 66
AMPS (Starting/Running)	Evaporator: 2/1, Condenser: 11/4	Evaporator: 2/1, Condenser: 15/10	Evaporator: 2/1, Condenser: 18/9
dBA (Evaporator/Condenser)	51/65	54/65	54/65
Line Set	3/8" Suction, 1/4" Liquid	1/2" Suction, 1/4" Liquid	1/2" Suction, 1/4" Liquid
Drainline	1/2" Condensate		
Installation	Evaporator coil installed in the cellar or up to 8 feet ducted. Condenser up to 100 line feet away. Follow owners manual specifications		
Thermostat	Advanced electronic control system		
Temp. Delta	55° F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 110°F)		
Warranty	2 year parts and labor		

Optional Accessories

Exterior condenser housing

