

# Classic Plus 14

MOVINCOOL®  
THE #1 SPOT COOLING SOLUTION

The MovinCool Classic Plus 14 portable air conditioner has all the benefits of our proven Classic Series, PLUS new features designed to increase performance and control. The versatile Classic Plus is instantly ready to provide cool air in the hottest environments such as production lines, outdoor events, manufacturing processes, injection molding, metal forming and much more.

The Classic Plus features a programmable digital temperature controller allowing the user to "set" the desired temperature. By cooling only the area that needs it, the Classic Plus 14 portable air conditioner saves you money while protecting people and equipment and speeding up processes. Self-contained and portable, the Classic Plus 14 requires little or no installation - simply roll it in, plug it in and turn it on.

- Programmable digital temperature control. Set the desired temperature and walk away
- Operates on standard 115V power. Can be used anywhere for as little as 15 cents per hour
- Provides up to 13,200 Btu/h of cool air. Maximum spot cooling to just the spot that needs it
- Handles temperatures up to 113°F. Provides cooling in the hottest environments



# MOVINCOOL®

THE #1 SPOT COOLING SOLUTION

800.264.9573  
www.movincool.com

DENSO SALES CALIFORNIA, Inc. 3900 Via Oro Ave. Long Beach, CA 90810



TECHNICAL SPECS		CLASSIC PLUS 14
Electronic Features	Control	Programmable
Cooling Capacity	Rating Conditions: 95°F at 60% RH	13,200 Btu/h
Electrical Characteristics	Voltage Requirements Total Power Consumption Current Consumption Recommended Fuse Size NEMA Plug Configuration Min. – Max. Voltage	1 Phase, 115V 1.3 kW 11.9 amps 15 amps 5 -15 105 - 125
Fans	Motor Output - high/low	0.24/0.19 kW
Evaporator	Fan Type Max. Air Flow - high/low Max. External Static Pressure	Centrifugal 440/380 CFM 0.31 IWG
Condenser	Fan Type Max. Air Flow - high/low Max. External Static Pressure	Centrifugal 880/760 CFM 0.19 IWG
Compressor	Type Output	Hermetic Rotary 0.9 kW
Refrigerant	Type	R-410A
Dimensions	W x D x H	19 x 26 x 41 in
Net Weight/Shipping Weight		166/197 lb
Power Cord	Gauge/Length	14 AWG (3-core)/10 ft
Condensate Tank Capacity		5 gal
Operating Conditions	Min. – Max. (@ 50% RH)	70° - 113°F
Max. Equivalent Duct Length	Per Cold Duct Hose Hot Duct Hose	30 ft 60 ft
Max. Sound Level	With Condenser - Duct high/low Without Condenser - Duct high/low	57/55 dB(A) 60/58 dB(A)

All specifications subject to change without notice.

© 2013 DENSO SALES CALIFORNIA, INC. MovinCool, SpotCool and Office Pro are registered trademarks of DENSO Corporation.  
360-0213-CP14

