

Office Pro® 63

MOVINCOOL®
THE #1 SPOT COOLING SOLUTION

Providing up to 60,000 Btu/h of computer cooling capacity (more than twice the cooling power of the Office Pro 24), the Office Pro 63 portable air conditioner is specifically designed for cooling large office spaces and computer rooms that house heat-generating electronics. As an ideal server room air conditioner, it prevents computer networks, communications, and office equipment from shutting down when temperatures rise.

Avoid crippling daily operations by bringing portable A/C to just the area or room that needs it. Protect critical data from being lost with an Office Pro 63. This powerful computer room air conditioner saves you money while protecting your company's investment in equipment, employees and customers.

- Operates on 3 Phase, 460V electric, providing ultimate flexibility in cooling and power options
- Provides 60,000 Btu/h of cool air, maximum spot cooling to just the room that needs it
- No costly installation necessary, simply roll it in, plug it in and turn it on
- Condensation pump included, pumps water to remote drain for uninterrupted operation



MOVINCOOL®

THE #1 SPOT COOLING SOLUTION

800.264.9573
www.movincool.com

DENSO SALES CALIFORNIA, Inc. 3900 Via Oro Ave. Long Beach, CA 90810



| TECHNICAL SPECS | | OFFICE PRO® 63 |
|-----------------------------|---|---|
| Electronic Features | Control | Programmable |
| Cooling Capacity | Rating Conditions: 95°F at 60% RH | 60,000 Btu/h |
| Electrical Characteristics | Voltage Requirements Total Power Consumption Current Consumption Recommended Fuse Size NEMA Plug Configuration Min. – Max. Voltage | 3 Phase, 460V 6.6 kW 9.5 amps 20 amps L16 - 20 440 - 480 |
| Fans | Motor Output - high/low | 0.5/0.33 kW (Evaporator) 1.2/0.93 kW (Condenser) |
| Evaporator | Fan Type Max. Air Flow - high/low Max. External Static Pressure | Centrifugal 1940/1770 CFM 0.9 IWG |
| Condenser | Fan Type Max. Air Flow - high/low Max. External Static Pressure | Centrifugal 2830/2650 CFM 0.85 IWG |
| Compressor | Type Output | Hermetic Scroll 3.3 kW |
| Refrigerant | Type | R-410A |
| Dimensions | W x D x H | 30 x 52 x 64 in |
| Net Weight/Shipping Weight | | 705/835 lb |
| Power Cord | Gauge/Length | 12 AWG (4-core)/6 ft |
| Condensate Tank Capacity | | Auto Pump Included |
| Operating Conditions | Min. – Max. (@ 50% RH) | 65° - 105°F |
| Max. Equivalent Duct Length | Per Cold Duct Hose Hot Duct Hose | 40 ft 100 ft |
| Max. Sound Level | With Condenser - Duct high/low Without Condenser - Duct high/low | 69/67 dB(A) 71/69 dB(A) |

All specifications subject to change without notice.

© 2013 DENSO SALES CALIFORNIA, INC. MovinCool, SpotCool and Office Pro are registered trademarks of DENSO Corporation.
360-0213-0P63

