

QUICK-SLING

The safe & affordable install

Applicable for residential or light commercial installations



How would you attach a mini-split unit to the side of a building be it concrete, brick, wood or vinyl?

How much time would it take you to collect the materials & install a comparable platform?

We are glad to introduce to you Quick-Sling, LLC., a line of hangers & stands that provides a sturdy platform for furnaces & air-handlers within residential & light commercial use.

Our goal is to save you time & money so that YOU HAVE MORE TIME TO MAKE MORE MONEY.

Quick-Sling Wall Bracket SPECS QSWB 1000 Wall Bracket



The QSWB 1000 is made of 14-gauge square, steel tubing which cuts down on vibration & is able to hold up to 300 lbs.



Two spacer bars snap into place with a saddle on each end. The J-bars attaches at 32" to 48" for the perfect fit.

The QSWB 1000 is able to be installed down & out or up & out.

All three dimensions:
Bracket Height: 16 1/2"
Bracket Depth: 22 1/4"
Min/Max Width: 32" to 48"



The QSWB 1000 includes anti-vibration isolation using 16 50-derometer rubber washers.



It also incorporates galvanized hardware to secure the unit to the wall bracket.

Four multi-positional clips for easy mounting is standard.

Patent Pending

Quick-Sling provides you with a non-swinging, solid platform that is quick, safe, stable and affordable.

Quick-Sling, LLC. – the HVAC installation that installs in minutes

The Quick-Sling advantage:

- › Installation is quick
- › Passes inspections in all 50 states
- › Quick-Sling is powder coated to last
- › Provides a safe & secure foundation
- › All necessary hardware is provided
- › Adjustable for virtually all applications

QUICK-SLING

391 West Water Street
Taunton, MA 02780
Phone: 1.800.699.0453
Fax: 1.800.699.0423
www.Quick-Sling.com