

Classic 10

MOVINCOOL®
THE #1 SPOT COOLING SOLUTION

At home in an office or in the warehouse, the Classic 10 portable air conditioner is the original portable air conditioner. It has no special power requirement so the Classic 10 can be rolled into any room and it's instantly ready to cool the hottest spot. By cooling only the area that needs it, the Classic 10 saves you money while protecting people and equipment and speeding up processes.

Self-contained and portable, the Classic 10 requires little or no installation, simply roll it in, plug it in and turn it on.

- Provides 10,000 Btu/h of cool air
- Operates on standard 115V. Roll it into any room that needs it
- Handles temperatures up to 105°F. Provides cooling in the hottest environments
- Half the cost of central air conditioning, cooling for as little as 15 cents per hour
- Rugged design, proven durability since 1982



MOVINCOOL®

THE #1 SPOT COOLING SOLUTION

800.264.9573
www.movincool.com

DENSO SALES CALIFORNIA, Inc. 3900 Via Oro Ave. Long Beach, CA 90810



| TECHNICAL SPECS | | CLASSIC 10 |
|-----------------------------|---|--|
| Electronic Features | Control | Digital |
| Cooling Capacity | Rating Conditions: 95°F at 60% RH | 10,000 Btu/h |
| Electrical Characteristics | Voltage Requirements Total Power Consumption Current Consumption Recommended Fuse Size NEMA Plug Configuration Min. – Max. Voltage | 1 Phase, 115V 1.1 kW 10 amps 15 amps 5 - 15 105 - 125 |
| Fans | Motor Output - high/low | 0.15 kW |
| Evaporator | Fan Type Max. Air Flow - high/low Max. External Static Pressure | Centrifugal 265 CFM 0.33 IWG |
| Condenser | Fan Type Max. Air Flow - high/low Max. External Static Pressure | Centrifugal 740 CFM 0.13 IWG |
| Compressor | Type Output | Hermetic Rotary 0.7 kW |
| Refrigerant | Type | R-410A |
| Dimensions | W x D x H | 19 x 26 x 41 in |
| Net Weight/Shipping Weight | | 156/194 lb |
| Power Cord | Gauge/Length | 14 AWG (3-core)/10 ft |
| Condensate Tank Capacity | | 5 gal |
| Operating Conditions | Min. – Max. (@ 50% RH) | 70° - 105°F |
| Max. Equivalent Duct Length | Per Cold Duct Hose Hot Duct Hose | 40 ft 60 ft |
| Max. Sound Level | With Condenser - Duct high/low Without Condenser - Duct high/low | 53 dB(A) 58 dB(A) |

All specifications subject to change without notice.

© 2013 DENSO SALES CALIFORNIA, INC. MovinCool, SpotCool and Office Pro are registered trademarks of DENSO Corporation.

360-0213-C10

