



All Models	A 12"	B 47"	C 12"
------------	----------	----------	----------

Key Features

- Great for contractors building custom systems
- Flexible wall mount or ceiling joist mount options
- Black exterior that hides coil behind wood grill
- May be ducted up to 8 feet away from cellar
- Extremely quiet in cellar operation
- 55 degree temperature differential
- Adjustable fan speed control

Specifications

Model	HM2500-C	HM3500-C	HM5000-C	HM6500-C
Cellar Size (Cu. Ft.)	650	1000	1500	2000
BTUh @ 55°	3100	3500	≈4100	6500
CFM	214	252	456	456
Dimensions	47"W x 12"H x 12"D			
Refrigerant	R-134a	R-134a	R-134a	R-134a
HP	1/4	1/3	1/3++	1/2
Voltage Rating (20 amp dedicated circuit required)	110V or 220V	110V or 220V	110V or 220V	110V or 220V
Weight (lbs)	60	60	65	65
AMPS (Starting/Running)	1.4/1.04	1.4/1.14	2.5/2	2.5/2.1
dBa (Evaporator)	48	56	56	59
Drainline	1/2" Condensate			
Installation	Evaporator coil installed in the cellar or up to 8 feet away			
Thermostat	Optional advanced electronic control system			
Temp. Delta	55°F			
Suggested Condenser	Tecumseh: AEA3430YXASC Copeland: M2FH-0026-IAA-072	Tecumseh: AEA4440YXASC Copeland: M2FH-A033-IAA-272	Tecumseh: AEA4448YXASC Copeland: M2FH-0049-IAA-201	Tecumseh: AKA4476YXASC Copeland: M2FH-A056-IAA-272
Warranty	2 year parts and labor			

Optional Accessories

Advanced electronic control system, duct kit

