



All Models **A** 12" **B** 47" **C** 12"

Key Features

- Great for contractors building custom systems
- Flexible wall mount or ceiling joist mount options
- Black exterior to hide unit behind wood grill
- May be ducted up to 8 feet from cellar
- Extremely quiet in cellar operation
- 55 degree temperature differential
- Adjustable fan speed control

Specifications

Model	HM7000-C	HM7600-C	HM8200-C	HM10600-C	HM13000-C
Cellar Size (Cu. Ft.)	2250	2500	3000	3500	4000
BTUh @ 55°	7232	7824	8140	10,700	13,930
CFM	214 + 214	214 + 456	456 + 456	456 + 456	456 + 456
Units	HM3500 + HM3500	HM3500 + HM5000	HM5000 + HM5000	HM5000 + HM6500	HM6500 + HM6500
Dimensions	47"W x 12"H x 12"D (2 units)				
Refrigerant	R134a	R134a	R134a	R134a	
HP	1/4 + 1/4	1/4 + 1/3	1/3 + 1/3	1/3 + 1/2	1/2 + 1/2
Voltage Rating (20 amp dedicated circuit required)	120V	120V	120V	220V	220V
Weight (lbs)	60 + 60	60 + 60	60 + 65	65 + 65	65 + 65
Drainline	1/2" Condensate				
Installation	Evaporator coil installed in the cellar or up to 8 feet away				
Thermostat	Optional advanced electronic control system				
Temp. Delta	55°F				
Suggested Condenser	Tecumseh: AJA4492YXAXC	Copeland: ETAH-A075-IAA-212	Copeland: M2FH-0074-CFA-212	Tecumseh: AJA4512YXDXC	Copeland: CTAH-0150-CAV-001
Warranty	2 year parts and labor				

Optional Accessories

Advanced electronic control system, duct kit

