



## 1. PRODUCT AND COMPANY IDENTIFICATION

#### Company

Arkema Inc. 900 First Avenue King of Prussia, Pennsylvania 19406

**Fluorochemicals** 

**Customer Service Telephone Number:** (800) 245-5858

(Monday through Friday, 8:30 AM to 5:30 PM EST)

**Emergency Information** 

Transportation: CHEMTREC: (800) 424-9300

(24 hrs., 7 days a week)

Medical: Rocky Mountain Poison Center: (866) 767-5089

(24 hrs., 7 days a week)

**Product Information** 

Product name: FORANE ® 409A

Synonyms: R-409A, HCFC 409A, FORANE FX 56
Molecular formula: CHCIF2/CHCLFCF3/CH3CCIF2
Chemical family: Hydrochlorofluorocarbon

Molecular weight: 97.43 g/mol Product use: 97.43 g/mol Refrigerant

### 2. HAZARDS IDENTIFICATION

#### **Emergency Overview**

Color: Clear - colourless

Physical state: gas

Form: Liquefied gas
Odor: Slightly ether-like

**CAUTION!** 

HIGH PRESSURE GAS.

LIQUID AND GAS UNDER PRESSURE.

OVERHEATING OR OVERPRESSURIZING MAY CAUSE GAS RELEASE OR VIOLENT CYLINDER BURSTING. MAY DECOMPOSE ON CONTACT WITH FLAMES OR EXTREMELY HOT METAL SURFACES TO PRODUCE TOXIC AND CORROSIVE PRODUCTS.

VAPOR REDUCES OXYGEN AVAILABLE FOR BREATHING AND IS HEAVIER THAN AIR.

MAY CAUSE SKIN IRRITATION.

MAY CAUSE FROSTBITE.

MAY CAUSE HEADACHE, NAUSEA, DIZZINESS, DROWSINESS, LOSS OF CONSCIOUSNESS.

**MAY CAUSE EFFECTS ON: HEART** 

## **Potential Health Effects**

Primary routes of exposure:

Inhalation and skin contact.

Product code: 04010 Version 2.0 Issued on: 07/11/2011 Page: 1 / 14



# **FORANE ® 409A**

### Signs and symptoms of acute exposure:

May cause skin irritation. Liquid: Rapid evaporation of the liquid may cause frostbite. Vapor: Vapor is heavier than air and can cause suffocation by reducing oxygen available for breathing. Central nervous system effects: headache, nausea, dizziness, drowsiness, loss of consciousness. Stress induced heart effects: irregular heart beat, rapid heart beat, (severity of effects depends on extent of exposure).

#### Skin:

Moderately irritating. (based on components) May cause frostbite. (direct contact)

#### Inhalation:

Practically nontoxic. (based on components)

#### Eves

Slightly irritating. (based on components) Causes frostbite burns to eyes. (mist or aerosol)

### Medical conditions aggravated by overexposure:

Heart disease or compromised heart function.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No.	Wt/Wt	OSHA Hazardous
Methane, chlorodifluoro-	75-45-6	60 %	Υ
Ethane, 2-chloro-1,1,1,2-tetrafluoro-	2837-89-0	25 %	Υ
Ethane, 1-chloro-1,1-difluoro-	75-68-3	15 %	Υ
Ethane, 1-chloro-1,1,2,2-tetrafluoro-	354-25-6	< 5 %	Υ

The substance(s) marked with a "Y" in the Hazard column above, are those identified as hazardous chemicals under the criteria of the OSHA Hazard Communication Standard (29 CFR 1910.1200).

This material is classified as hazardous under Federal OSHA regulation.

#### 4. FIRST AID MEASURES

#### Inhalation:

If inhaled, remove victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

#### Skin


If on skin, flush exposed skin with lukewarm water (not hot), or use other means to warm skin slowly. Remove contaminated clothing and shoes. Get medical attention if frostbitten by liquid or if irritation occurs. Wash clothing before reuse. Thoroughly clean shoes before reuse.

### Eyes:

Immediately flush eye(s) with plenty of water.

### Ingestion:

Ingestion is not applicable - product is a gas at ambient temperatures.





### Notes to physician:

Do not give drugs from adrenaline-ephedrine group.

## 5. FIRE-FIGHTING MEASURES

Flash point Not applicable

Auto-ignition temperature: not determined

Lower flammable limit (LFL): None.

Upper flammable limit (UFL): None.

### Extinguishing media (suitable):

Use extinguishing measures to suit surroundings.

### Protective equipment:

Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand / NIOSH approved or equivalent). Fire fighting equipment should be thoroughly decontaminated after use.

### Further firefighting advice:

Keep containers cool by spraying with water if exposed to fire.

Water mist should be used to reduce vapor concentrations in air.

### Fire and explosion hazards:

May decompose on contact with flames or extremely hot metal surfaces to produce toxic and corrosive products. Liquid and gas under pressure, overheating or overpressurizing may cause gas release and/or violent cylinder bursting.

Container may explode if heated due to resulting pressure rise.

Some mixtures of HCFCs and/or HFCs, and air or oxygen may be combustible if pressurized and exposed to extreme heat or flame.

When burned, the following hazardous products of combustion can occur:

Hydrogen fluoride

hydrogen chloride

# **6. ACCIDENTAL RELEASE MEASURES**

## In case of spill or leak:

Use Halogen leak detector or other suitable means to locate leaks or check atmosphere. Keep upwind. Evacuate enclosed spaces and disperse gas with floor-level forced-air ventilation. Stop the leak if you can do so without risk. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

Product code: 04010 Version 2.0 Issued on: 07/11/2011 Page: 3 / 14



# **FORANE ® 409A**

## 7. HANDLING AND STORAGE

## **Handling**

### General information on handling:

Avoid breathing gas.

Keep container closed.

Use only with adequate ventilation.

Do not enter confined spaces unless adequately ventilated.

Use equipment rated for cylinder pressure.

Use a backflow preventative device in piping.

Wash thoroughly after handling.

Close valve after each use and when empty.

Emptied container retains vapor and product residue.

Observe all labeled safeguards until container is cleaned, reconditioned or destroyed.

## **Storage**

### General information on storage conditions:

Store in well ventilated area away from heat and sources of ignition such as flame, sparks and static electricity.

### Storage stability - Remarks:

Do not apply direct flame to cylinder. Do not store cylinder in direct sun or expose it to heat above 120 F (48.9 C.). Do not drop or refill this cylinder.

### Storage incompatibility - General:

Keep away from oxidising agents and strongly acid or alkaline materials.

## Temperature tolerance – Do not store above:

118 °F (48 °C)

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## **Airborne Exposure Guidelines:**

## Methane, chlorodifluoro- (75-45-6)

US. ACGIH Threshold Limit Values

Time Weighted Average (TWA): 1,000 ppm

# Ethane, 2-chloro-1,1,1,2-tetrafluoro- (2837-89-0)

US. Workplace Environmental Exposure Level (WEEL) Guides

Time Weighted Average (TWA): 1,000 ppm

Remarks: Listed

# Ethane, 1-chloro-1,1-difluoro- (75-68-3)

US. Workplace Environmental Exposure Level (WEEL) Guides

Product code: 04010 Version 2.0 Issued on: 07/11/2011 Page: 4 / 14



# **FORANE ® 409A**

Time Weighted Average (TWA): 1,000 ppm (4,100 mg/m3)

Remarks: Listed

Only those components with exposure limits are printed in this section. Limits with skin contact designation above have skin contact effect. Air sampling alone is insufficient to accurately quantitate exposure. Measures to prevent significant cutaneous absorption may be required. Limits with a sensitizer designation above mean that exposure to this material may cause allergic reactions.

## **Engineering controls:**

Investigate engineering techniques to reduce exposures below airborne exposure limits or to otherwise reduce exposures. Provide ventilation if necessary to minimize exposures or to control exposure levels to below airborne exposure limits (if applicable see above). Provide ventilation if necessary to control exposure levels below airborne exposure limits (see above). If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

### Respiratory protection:

Avoid breathing gas. Where airborne exposure is likely or airborne exposure limits are exceeded (if applicable, see above), use NIOSH approved respiratory protection equipment appropriate to the material and/or its components (full facepiece recommended). Consult respirator manufacturer to determine appropriate type equipment for a given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where there may be a potential for significant exposure or where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

## Skin protection:

Wear appropriate chemical resistant protective clothing and chemical resistant gloves to prevent skin contact. Consult glove manufacturer to determine appropriate type glove material for given application. Rinse immediately if skin is contaminated. Wash contaminated clothing and clean protective equipment before reuse. Wash thoroughly after handling.

#### Eye protection:

Use good industrial practice to avoid eye contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Color: Clear - colourless

Physical state: gas

Form: Liquefied gas

Odor: Slightly ether-like

pH: not applicable

**Density:** not determined

Specific Gravity (Relative 1.21 (77 °F( 25 °C))

Product code: 04010 Version 2.0 Issued on: 07/11/2011 Page: 5 / 14



# **FORANE ® 409A**

density):

**Vapor pressure:** 5,388 mmHg (70.0 °F (21.1 °C))

Vapor density: 3.38 kg/m3

**Boiling point/boiling** 

range:

-24 °F (-31 °C)

Freezing point: not determined

Melting point: not determined

Solubility in water: negligible

**% Volatiles:** 100 %

Molecular weight: 97.43 g/mol

## 10. STABILITY AND REACTIVITY

### Stability:

This material is chemically stable under normal and anticipated storage, handling and processing conditions.

### Materials to avoid:

Strong oxidizing agents Strong acids Alkaline materials

### Conditions / hazards to avoid:

Heat.

# Hazardous decomposition products:

Thermal decomposition giving toxic and corrosive products : Halogen acids (HCl and HF)
Carbon monoxide
Carbon dioxide (CO2)
Carbonyl halides

## 11. TOXICOLOGICAL INFORMATION

Data on this material and/or its components are summarized below.

# Data for Methane, chlorodifluoro- (75-45-6)

## **Acute toxicity**

Inhalation:

Practically nontoxic. (rat) 4 h LC50 approx. 780 mg/l (220000 ppm).

Skin Irritation:

Moderately irritating. (rabbit) (Rapid evaporation of the liquid may cause frostbite.)

Product code: 04010 Version 2.0 Issued on: 07/11/2011 Page: 6 / 14



# **FORANE ® 409A**

### Eye Irritation:

Slightly irritating. (rabbit) (30 s) (gas spray)

#### Sensitization:

Causes cardiac sensitization. (dog, rat, mouse, rabbit and monkey) irregular heart beat, rapid heart beat, in some cases, sudden death

#### Skin Sensitization:

Repeated skin exposure. (guinea pig) No skin allergy was observed

### Repeated dose toxicity

Repeated inhalation administration to rat, rabbit, mouse / affected organ(s): liver, lung, central nervous system / (Repeated exposure at high concentrations)

Chronic oral administration to rat / No adverse effects reported.

### Carcinogenicity

Chronic inhalation administration to mouse / No increase in tumor incidence was reported.

Chronic inhalation administration to female rat / No increase in tumor incidence was reported.

Chronic inhalation administration to male rat / affected organ(s): salivary gland / Increased incidence of tumors was reported. (The observed tumors do not appear to be relevant for men.)

### **Genotoxicity**

#### Assessment in Vitro:

Genetic changes were observed in laboratory tests using: bacteria

No genetic changes were observed in laboratory tests using: animal cells, yeast

#### Genotoxicity

#### Assessment in Vivo:

No genetic changes were observed in laboratory tests using: animals, rodent

## **Developmental toxicity**

Exposure during pregnancy. inhalation (rat) / Birth defects were observed. (eye) Exposure during pregnancy. inhalation (rabbit) / No birth defects were observed.

### Reproductive effects

Reproduction test. inhalation (rat and mouse) / No toxicity to reproduction / (males)

### **Human experience**

#### Inhalation:

Lung: Asphyxia, suffocation.

Heart: Palpitation. (based on reports of occupational exposure to workers)

### <u>Human experience</u>

### Skin contact:

Skin: irritation, redness, swelling. (repeated or prolonged exposure)

Product code: 04010 Version 2.0 Issued on: 07/11/2011 Page: 7 / 14



# **FORANE ® 409A**

### Data for Ethane, 2-chloro-1,1,1,2-tetrafluoro- (2837-89-0)

### **Acute toxicity**

### Inhalation:

Practically nontoxic. (rat) 4 h LC50 between 1,280 - 1,670 mg/l (between 230000 - 300000 ppm).

Signs/effects reported after acute exposure. (dog, mouse) signs: anesthetic effects

#### Sensitization:

Causes cardiac sensitization. Inhalation. (dog) Stress induced heart effects: irregular heart beat, rapid heart beat, in some cases, sudden death (Reaction may occur in response to stress (natural adrenaline release) or administration of epinephrine.)

## Repeated dose toxicity

Inhalation administration to rat and mouse / affected organ(s): central nervous system / signs: blood chemistry changes

## Carcinogenicity

Chronic inhalation administration to rat / No increase in tumor incidence was reported.

### **Genotoxicity**

#### Assessment in Vitro:

No genetic changes were observed in laboratory tests using: bacteria, animal cells

### Genotoxicity

#### Assessment in Vivo:

No genetic changes were observed in laboratory tests using: animals

## **Developmental toxicity**

Exposure during pregnancy. inhalation (rat and rabbit) / No birth defects were observed. (at doses that produce effects in mothers)

# Data for Ethane, 1-chloro-1,1-difluoro- (75-68-3)

### **Acute toxicity**

#### Inhalation:

Practically nontoxic. (rat) 6 h LC50 > 400,000 ppm. signs: respiratory irritation

### Eye Irritation:

Slightly irritating. (rabbit) (liquid)

### Sensitization:

Causes cardiac sensitization. Inhalation. (dog) Stress induced heart effects: irregular heart beat, rapid heart beat, in some cases, sudden death (Reaction may occur in response to stress (natural adrenaline release) or administration of epinephrine.)

### Carcinogenicity

Chronic inhalation administration to rat / No increase in tumor incidence was reported.

### Genotoxicity



# **FORANE ® 409A**

#### Assessment in Vitro:

Both positive and negative responses for genetic changes were observed in laboratory tests using: bacteria, animal cells

## **Genotoxicity**

#### **Assessment in Vivo:**

No genetic changes were observed in laboratory tests using: animals

#### **Developmental toxicity**

Exposure during pregnancy. inhalation (rat) / No birth defects were observed.

### Reproductive effects

Repeated administration. Inhalation (rat, dog) / Did not cause damage to the reproductive organs.

Exposure prior to mating. Inhalation (mouse) / No toxicity to reproduction / (males)

## 12. ECOLOGICAL INFORMATION

### **Chemical Fate and Pathway**

Data on this material and/or its components are summarized below.

## Data for Methane, chlorodifluoro- (75-45-6)

## **Biodegradation:**

Not readily biodegradable.

### Octanol Water Partition Coefficient:

log Pow = 1.08 (Practically no potential to bioaccumulate.)

### Photodegradation:

Half-life direct photolysis: = 8.4 y

### Mobility and Distribution in the Environment:

Moderate adsorption / Log Koc = 1.8

# **Global Warming Potential:**

GWP = 0.33 (Halocarbon global warming potential.)

### **Ozone Depletion Potential:**

ODP = 0.055

## Data for Ethane, 2-chloro-1,1,1,2-tetrafluoro- (2837-89-0)

### **Biodegradation:**

Not readily biodegradable. (28 d) biodegradation 2 - 5 %

Slight potential to bioaccumulate.

## **Octanol Water Partition Coefficient:**

log Pow = 1.9 - 2.0

# Global Warming Potential:

GWP 470 (Global warming potential with respect to CO2 (time horizon 100 years))

Product code: 04010 Version 2.0 Issued on: 07/11/2011 Page: 9 / 14



## **Ozone Depletion Potential:**

ODP approx. 0.02 (Ozone depletion potential; ODP; (R-11 = 1))

## Data for Ethane, 1-chloro-1,1-difluoro- (75-68-3)

#### **Biodegradation:**

Not readily biodegradable. (20 d) biodegradation 5 %

Practically no potential to bioaccumulate.

## **Octanol Water Partition Coefficient:**

log Pow = 1.64 - 2.05

## Photodegradation:

Half-life direct photolysis: = 12.8 y

## **Global Warming Potential:**

GWP = 0.42 (Halocarbon global warming potential.)

GWP = 1,800 (CO2)

### **Ozone Depletion Potential:**

ODP = 0.065

### **Ecotoxicology**

Data on this material and/or its components are summarized below.

### Data for Methane, chlorodifluoro- (75-45-6)

### Aquatic toxicity data:

Practically nontoxic. Fish 24 h Toxicity threshold = 180 mg/l

## Microorganisms:

Slightly toxic. under anaerobic conditions / Bacteria 24 h Toxicity threshold > 400 mg/l

## Data for Ethane, 1-chloro-1,1-difluoro- (75-68-3)

### Aquatic toxicity data:

Practically nontoxic. Poecilia reticulata (guppy) 96 h LC50 = 220 mg/l

## Aquatic invertebrates:

Practically nontoxic. Daphnia magna (Water flea) 48 h EC50 >= 160 mg/l Practically nontoxic. Daphnia magna (Water flea) 48 h EC50 > 190 mg/l

Product code: 04010 Version 2.0 Issued on: 07/11/2011 Page: 10 / 14



# **FORANE ® 409A**

## 13. DISPOSAL CONSIDERATIONS

#### Waste disposal:

Do not vent the container contents, or product residuals, to the atmosphere. Recover and reclaim unused contents or residuals as appropriate. Recovered/reclaimed product can be returned to an approved certified reclaimer or back to the seller depending on the material. Completely emptied disposable containers can be disposed of as recyclable steel. Returnable cylinders must be returned to seller. Dispose of in accordance with federal, state and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

## 14. TRANSPORT INFORMATION

## **US Department of Transportation (DOT)**

UN Number : 3163

Proper shipping name : Liquefied gas, n.o.s.

Technical name : (Chlorodifluoromethane, 1-Chloro-1,1-difluoroethane)

Class : 2.2 Marine pollutant : no

## International Maritime Dangerous Goods Code (IMDG)

UN Number : 3163

Proper shipping name : LIQUEFIED GAS, N.O.S.

Technical name : (CHLORODIFLUOROMETHANE, 1-CHLORO-1,1-

DIFLUOROETHANE)

Class : 2.2 Marine pollutant : no

## 15. REGULATORY INFORMATION

## **Chemical Inventory Status**

EU. EINECS EINECS Conforms to

US. Toxic Substances Control Act TSCA The components of this product are all on

the TSCA Inventory.

Australia. Industrial Chemical (Notification and AICS Conforms to

Assessment) Act

Canada. Canadian Environmental Protection Act DSL All components of this product are on the

(CEPA). Domestic Substances List (DSL). (Can. Gaz. Canadian DSL list.

Part II, Vol. 144)

Japan. Kashin-Hou Law List ENCS (JP) Does not conform

Korea. Existing Chemicals Inventory (KECI) KECI (KR) Conforms to





Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	PICCS (PH)	Conforms to
China. Inventory of Existing Chemical Substances	IECSC (CN)	Conforms to
China. Inventory of Existing Chemical Substances	IECSC (CN)	Conforms to
New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand	NZIOC	Does not conform

## <u>United States – Federal Regulations</u>

## SARA Title III - Section 302 Extremely Hazardous Chemicals:

The components in this product are either not SARA Section 302 regulated or regulated but present in negligible concentrations.

## SARA Title III - Section 311/312 Hazard Categories:

Acute Health Hazard, Sudden Release of Pressure Hazard

## SARA Title III - Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	De minimis concentration	Reportable threshold:	
Methane, chlorodifluoro-	75-45-6		1.0 %	10000 lbs (Otherwise used (non-manufacturing/processing)) 25000 lbs (Manufacturing and processing)
Ethane, 1-chloro-1,1-difluoro-	75-68-3		1.0 %	10000 lbs (Otherwise used (non-manufacturing/processing)) 25000 lbs (Manufacturing and processing)
Ethane, 2-chloro-1,1,1,2-tetrafluoro-	2837-89-0		1.0 %	10000 lbs (Otherwise used (non-manufacturing/processing)) 25000 lbs (Manufacturing and processing)
Ethane, 1-chloro-1,1,2,2-tetrafluoro-	354-25-6		1.0 %	10000 lbs (Otherwise used (non-manufacturing/processing)) 25000 lbs (Manufacturing and processing)

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantity (RQ):



# **FORANE ® 409A**

The components in this product are either not CERCLA regulated, regulated but present in negligible concentrations, or regulated with no assigned reportable quantity.

## OSHA Regulated Carcinogens (NTP, IARC, OSHA Listed):

#### NTP:

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

#### IARC:

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

#### OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

## **United States - State Regulations**

## **New Jersey Right to Know**

Chemical Name	CAS-No.
Methane, chlorodifluoro-	75-45-6
Ethane, 1-chloro-1,1-difluoro-	75-68-3
Ethane, 2-chloro-1,1,1,2-tetrafluoro-	2837-89-0
Ethane, 1-chloro-1,1,2,2-tetrafluoro-	354-25-6

### Pennsylvania Right to Know

<u>Chemical Name</u> Methane, chlorodifluoro-	<u>CAS-No.</u> 75-45-6
Ethane, 1-chloro-1,1-difluoro-	75-68-3
Ethane, 2-chloro-1,1,1,2-tetrafluoro-	2837-89-0

## Pennsylvania Right to Know - Environmentally Hazardous Substance(s)

<u>Chemical Name</u>	CAS-No.
Methane, chlorodifluoro-	75-45-6

# California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive defects.

# **16. OTHER INFORMATION**

Latest Revision(s):

Revised Section(s): Updated Corporate Address Change and Rocky Mountain Poison

Center Phone Number

Reference number: 000000057863 Date of Revision: 07/11/2011

Product code: 04010 Version 2.0 Issued on: 07/11/2011 Page: 13 / 14



# **FORANE ® 409A**

Date Printed: 12/27/2012

FORANE ® is a registered trademark of Arkema Inc.

Arkema Inc. believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use are beyond the control of Arkema Inc., Arkema Inc. expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.