



All Models      A 47"      B 12"      C 12"

### Key Features

- Ready for "Plug n Play" installation
- Adjustable fan speed control
- Coil mounted in void corners of racking
- May be ducted up to 8 feet from cellar
- Black exterior to hide unit behind racking
- Extremely quiet in cellar operation
- 55 degree temperature differential

### Specifications

Model	VM7000-S	VM7600-S	VM8200-S	VM10600-S	VM13000-S
Cellar Size (Cu. Ft.)	2250	2500	3000	3500	4000
BTUh @ 55°	7232	7824	8140	10,700	13,930
CFM	214 + 214	214 + 456	456 + 456	456 + 456	456 + 456
Units	VM3500 + VM3500	VM3500 + VM5000	VM5000 + VM5000	VM5000 + VM6500	VM6500 + VM6500
Dimensions	12"W x 47"H x 12"D (2 units)				
Refrigerant	R134a	R134a	R134a	R134a	
HP	1/4 + 1/4	1/4 + 1/3	1/3 + 1/3	1/3 + 1/2	1/2 + 1/2
Voltage Rating (20 amp dedicated circuit required)	120V	120V	120V	220V	220V
Coil Weight (lbs)	60 + 60	60 + 60	60 + 65	65 + 65	65 + 65
Drainline	1/2" Condensate				
Installation	Evaporator coil installed in the cellar or up to 8 feet away				
Thermostat	Advanced electronic control system				
Temp. Delta	55°F				
Warranty	2 year parts and labor				

### Optional Accessories

Duct kit, exterior condenser housing

