



	A	B	C
WM2500-C	10.5"	20"	11.25"
WM3500-C	15.5"	20.5"	14.5"
WM5000-C	15.5"	20.5"	14.5"

Key Features

- Great for contractors building custom systems
- Flexible wall mounting coils
- Quiet & efficient in cellar operation
- 55 degree temperature differential
- Sleek black power coated finish
- Adjustable fan speed control

Specifications

Model	WM2500-C	WM3500-C	WM5000-C
Cellar Size (Cu. Ft.)	500	1000	2000
BTUh @ 55°	1620	4715	6006
CFM	94	270	278
Dimensions	20"W x 10.5"H x 11.25"D	20.5"W x 15.5"H x 14.5"D	
Refrigerant	R-134a	R-134a	R-134a
HP	1/5	1/2	1/2+
Voltage Rating (20 amp dedicated circuit required)	110V or 220V	110V or 220V	110V or 220V
Weight (lbs)	25	56	56
AMPS (Starting/Running)	2/1	2/1	2/1
dBA (Evaporator)	51	54	54
Drainline	1/2" Condensate		
Installation	Evaporator coil installed in the cellar		
Thermostat	Optional advanced electronic control system		
Temp. Delta	55°F		
Suggested Condenser	Tecumseh: AEB3417YXASC Copeland: M2FH-0020-IAA-121	Tecumseh: AEA4448YXASC Copeland: M2FH-0049-IAA-201	Tecumseh: AKA4460YXASC
Warranty	2 year parts and labor		

Optional Accessories

Advanced electronic control system

