

Classic 40

MOVINCOOL®
THE #1 SPOT COOLING SOLUTION

For larger applications, the MovinCool Classic 40 portable air conditioner can create flexible, mobile or temporary cooling in factories and warehouses. Using multiple T-section drops, you can customize an adaptable portable air conditioner solution for your manufacturing or assembly lines. Add an optional wagon kit or casters to the units and you can move the cool air as your assembly or process line changes.

By cooling only the area that needs it, the Classic 40 saves you money while protecting people and equipment and speeding up processes.

- Inexpensive to use. Operate for as little as 35 cents per hour
- 39,000 Btu/h cooling capacity to handle any hot spot
- Half the cost of central air conditioning, no costly installation is necessary
- Handles temperatures up to 115°F, provides cooling in the hottest environments
- Rugged design, proven durability since 1982





TECHNICAL SPECS		CLASSIC 40
Electronic Features	Control	Digital
Cooling Capacity	Rating Conditions: 95°F at 60% RH	39,000 Btu/h
Electrical Characteristics	Voltage Requirements Total Power Consumption Current Consumption Recommended Fuse Size NEMA Plug Configuration Min. – Max. Voltage	3 Phase, 220V 4.2 kW 14 amps 25 amps L15 - 30 198 - 250
Fans	Motor Output - high/low	0.75 kW (Evaporator) 0.40 kW (Condenser)
Evaporator	Fan Type Max. Air Flow - high/low Max. External Static Pressure	Centrifugal 1060 CFM 1.72 IWG
Condenser	Fan Type Max. Air Flow - high/low Max. External Static Pressure	Propeller 2650 CFM 0.05 IWG
Compressor	Type Output	Hermetic Scroll 2.3 kW
Refrigerant	Type	R-410A
Dimensions	W x D x H	26 x 43 x 38 in
Net Weight/Shipping Weight		344/396 lb
Power Cord	Gauge/Length	12 AWG (4-core)/6 ft
Condensate Tank Capacity		2 @ 5 gal (optional)
Operating Conditions	Min. – Max. (@ 50% RH)	75° - 115°F
Max. Equivalent Duct Length	Per Cold Duct Hose Hot Duct Hose	Varies 40 ft
Max. Sound Level	With Condenser - Duct high/low Without Condenser - Duct high/low	N/A 72 dB(A)

